AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Currently Amended) A back light unit, comprising:

a lamp housing having a first side and a second side opposite the first side; and

a plurality of lamps respectively having a low voltage electrode and a high voltage

electrode each at opposite ends of the lamp, the lamps arranged substantially parallel in the

lamp housing,

wherein the plurality of low voltage electrodes of odd-numbered lamps are disposed

at the first side and the plurality of high voltage electrodes of odd-numbered lamps are

disposed at the second side,

wherein the plurality of high voltage electrodes of even-numbered lamps are disposed

at the first side and the plurality of low voltage electrodes of even-numbered lamps are

disposed at the second side,

wherein a low voltage of a first an AC voltage is applied to the plurality of low

voltage electrodes of odd-numbered lamps at the first side and the plurality of low voltage

electrodes of even-numbered lamps at the second side a high voltage of the first AC voltage

is applied to the plurality of high voltage electrodes of odd-numbered lamps at the second

side, and

wherein a high voltage of a second the AC voltage is applied to the plurality of high

voltage electrodes of even-numbered lamps at the first side and the plurality of high voltage

electrodes of odd-numbered lamps at the second side a low voltage of the second AC voltage

is applied to the plurality of low voltage electrodes of even-numbered lamps at the second

side.

2

2. (Previously Presented) The back light unit according to claim 1, further comprising: a diffusion plate located on the lamp housing; and an optical sheet located on the diffusion plate.

- 3. (Previously Presented) The back light unit according to claim 1, wherein the plurality of low voltage electrodes and the plurality of high voltage electrodes of the lamps are respectively arranged in a zigzag fashion.
- 4. (Previously Presented) The back light unit according to claim 1, wherein the plurality of low voltage electrodes and the plurality of high voltage electrodes of the lamps are alternately arranged by N-number (where N is a positive integer more than 2).
 - 5. (Currently Amended) A liquid crystal display, comprising:

a back light unit having a lamp housing having a first side and a second side opposite the first side, a plurality of lamps respectively having a low voltage electrode and a high voltage electrode each at opposite ends of the lamp and arranged substantially parallel in the lamp housing; and

a liquid crystal panel disposed on the back light unit and having a plurality of liquid crystal cells arranged in a matrix form,

wherein the plurality of low voltage electrodes of odd-numbered lamps are disposed at the first side and the plurality of high voltage electrodes of odd-numbered lamps are disposed at the second side,

wherein the plurality of high voltage electrodes of even-numbered lamps are disposed at the first side and the plurality of low voltage electrodes of even-numbered lamps are disposed at the second side,

wherein a low voltage of a first an AC voltage is applied to the plurality of low voltage electrodes of odd-numbered lamps at the first side and the plurality of low voltage electrodes of even-numbered lamps at the second side a high-voltage of the first AC voltage is applied to the plurality of high voltage electrodes of odd-numbered lamps at the second side, and

wherein a high voltage of a second the AC voltage is applied to the plurality of high voltage electrodes of even-numbered lamps at the first side and the plurality of high voltage electrodes of odd-numbered lamps at the second side a low voltage of the second AC voltage is applied to the plurality of low voltage electrodes of even numbered lamps at the second side.

- 6. (Previously Presented) The liquid crystal display according to claim 5, wherein the plurality of low voltage electrodes and the plurality of high voltage electrodes of the lamps are respectively located in a zigzag fashion
- 7. (Previously Presented) The liquid crystal display according to claim 5, wherein the plurality of low voltage electrodes and the plurality of high voltage electrodes of the lamps are alternately arranged by N-number (where N is a positive integer more than 2).
 - 8. (Currently Amended) A back light unit, comprising:
 a lamp housing having a first side and a second side opposite the first side; and

a plurality of lamps respectively having a low voltage electrode and a high voltage electrode each at opposite ends of the lamp, the lamps arranged substantially parallel in the lamp housing,

wherein the lamps have odd-numbered N-number (where N is a positive integer more than 2) lamps and even-numbered N-number (where N is a positive integer more than 2) lamps alternately arranged by N-number (where N is a positive integer more than 2),

wherein the plurality of low voltage electrodes of odd-numbered N-number lamps are disposed at the first side and the plurality of high voltage electrodes of odd-numbered N-number lamps are disposed at the second side,

wherein the plurality of high voltage electrodes of even-numbered N-number lamps are disposed at the first side and the plurality of low voltage electrodes of even-numbered N-number lamps are disposed at the second side,

wherein a low voltage of a first an AC voltage is applied to the plurality of low voltage electrodes of odd-numbered N-number lamps at the first side and the plurality of low voltage electrodes of even-numbered lamps at the second side a high voltage of the first AC voltage is applied to the plurality of high voltage electrodes of odd-numbered N-number lamps at the second side, [[and]]

wherein a high voltage of a second the AC voltage is applied to the plurality of high voltage electrodes of even-numbered N-number lamps at the first side and the plurality of high voltage electrodes of odd-numbered lamps at the second side a low voltage of the second AC voltage is applied to the plurality of low voltage electrodes of even-numbered N-number lamps at the second side, and

wherein the odd-numbered lamps with the N-number are disposed adjacent to one another, and the even-numbered lamps with the N-number are disposed adjacent to one another.

9. (Currently Amended) A liquid crystal display, comprising:

a back light unit having a lamp housing having a first side and a second side opposite the first side, a plurality of lamps respectively having a low voltage electrode and a high voltage electrode each at opposite ends of the lamp and arranged substantially parallel in the lamp housing; and

a liquid crystal panel disposed on the back light unit and having a plurality of liquid crystal cells arranged in a matrix form,

wherein the lamps have odd-numbered N-number (where N is a positive integer more than 2) lamps and even-numbered N-number (where N is a positive integer more than 2) lamps alternately arranged by N-number (where N is a positive integer more than 2),

wherein the plurality of low voltage electrodes of odd-numbered N-number lamps are disposed at the first side and the plurality of high voltage electrodes of odd-numbered N-number lamps are disposed at the second side,

wherein the plurality of high voltage electrodes of even-numbered N-number lamps are disposed at the first side and the plurality of low voltage electrodes of even-numbered N-number lamps are disposed at the second side,

wherein a low voltage of a first an AC voltage is applied to the plurality of low voltage electrodes of odd-numbered N-number lamps at the first side and the plurality of low voltage electrodes of even-numbered N-number lamps at the second side a high voltage of the first AC voltage is applied to the plurality of high voltage electrodes of odd-numbered N-number lamps at the second side, [[and]]

wherein a high voltage of a second the AC voltage is applied to the plurality of high voltage electrodes of even-numbered N-number lamps at the first side and the plurality of high voltage electrodes of odd-numbered N-number lamps at the second side a low voltage of

the second AC voltage is applied to the plurality of low voltage electrodes of even-numbered

N-number lamps at the second side, and

wherein the odd-numbered lamps with the N-number are disposed adjacent to one another, and the even-numbered lamps with the N-number are disposed adjacent to one another.